

Features of NIPPON KINZOKU Coil Center

March 28, 2025
NIPPON KINZOKU CO., LTD.
ALES SECT.
Person in charge: Ishii

[1] Features of NIPPON KINZOKU Coil Center =Original products also supplied in small lots=

- ① Small lots support : Available from 50kg per lot (We're happy to discuss orders below 50kg per lot)
- ② Delivery term : Minimum delivery time: within 3-7 days (Availability may vary depending on the requested size, delivery destination and production status, etc., so please contact us before placing your order)
- ③ Inspection certificate : All products will be supplied with your specified width, and the Inspection certificate of NIPPON KINZOKU will be attached to the actual product
- ④ Sample support : We are happy to provide samples of a few meters, so please feel free to contact us.
- ⑤ Quality Assurance and Technical Service : We will be happy to provide a timely technical response as well as material from repeat orders.
- ⑥ Special quality materials are also available : We will also consider the best operation (small lot, short delivery time) for special quality materials by procuring dedicated base materials through discussions with you.

[2] Inventory list

- ◎ : 1 metric ton more & width 200mm or more
- : Less than 1 metric ton & width 200mm or more
- ◆ : Width less than 200mm. limited stock available

Foil Products Inventory

| Steel grade | SUS301 | | SUS304 | | | | | | SUS 430 |
|-------------------|----------------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------|
| | Finish H -TA | EH -TA | 1/2H -TA | 3/4H -TA | H -TA | H-TA -LD | EH -TA | BA | No.1 -TA |
| Thickness (mm) | Hardness 430 or more | 490 or more | 310 or more | 370 or more | 430 or more | 490 or more | 490 or more | 200 or less | In stock 294 |
| 0.020 | | | | | | | | | |
| 0.025 | | | | | ○ | | | | |
| 0.030 | | ○ | | | ◆ | | | | |
| 0.040 | | | | | ○ | | | | |
| 0.050 | ◎ | | | ◆ | ◎ | | | ○ | ○ |
| 0.060 | | | | | ○ | | | | |
| 0.070 | | | | | ◎ | | | | |
| 0.075 | | | | | | | | | |
| 0.080 | ◎ | ○ | ◎ | ◎ | ○ | | | ◎ | |
| 0.090 | | | | | | | | | |

Product Inventory

(Other than general-purpose stainless steel grades)

| Steel grade | SUS301 | SUS305 | | | SUS316L | |
|-------------------|----------------------------|----------------|----------------|----------------|----------------|----------------|
| | Finish EH -TA | No.1 | 1/2H | BA | EH -TA | BA |
| Thickness (mm) | Hardness 490 or more | 200 or less | 200 or less | 200 or less | 490 or more | 200 or less |
| 0.100 | ◎ | ○ | | | ○ | ○ |
| 0.120 | | | | | | |
| 0.125 | | | | | | |
| 0.130 | | | | | | |
| 0.150 | ○ | ◎ | | ◆ | | |
| 0.170 | | | | | | |
| 0.180 | | | | | | |
| 0.200 | ○ | | ○ | | ○ | ◎ |
| 0.250 | | | | | | |
| 0.300 | | | | | | |
| 0.350 | | | | | | |

Product Inventory (General-purpose stainless steel grades)

| Steel grade | SUS301 | | | | | | | | SUS304 | | | | | | | | SUS430 | | | | | | | |
|-------------------|----------------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------|----------------|----------------|----------------|
| | 1/2H | 3/4H | H | EH | 1/2H -TA | 3/4H -TA | H -TA | EH -TA | 1/2H | 3/4H | H | EH | 1/2H -TA | 3/4H -TA | H -TA | H-TA -LD | EH -TA | BA | 2B | 2D | No.1 -TA | BA | 2B | 2D |
| Thickness (mm) | Hardness 310 or more | 370 or more | 430 or more | 490 or more | 310 or more | 370 or more | 430 or more | 490 or more | 310 or more | 370 or more | 430 or more | 490 or more | 310 or more | 370 or more | 430 or more | 430 or more | 490 or more | 200 or less | 200 or less | 200 or less | In stock 298 | 200 or less | 200 or less | 200 or less |
| 0.100 | ◎ | ◎ | ◎ | | | | ◎ | | ○ | ◆ | ◎ | | ◎ | | ○ | | | ◆ | | | ◆ | ◆ | | |
| 0.120 | | | | ◆ | | | | | ○ | ◎ | ◎ | | | | | | | | | | | | | |
| 0.125 | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.130 | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.150 | ◎ | ○ | ○ | | | ○ | | ○ | ◎ | ◎ | ○ | | | | | ◎ | | ◆ | ◆ | ◎ | | ◎ | | |
| 0.170 | | | | | | | ○ | | | | | | | | | | | | | | | | | |
| 0.180 | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | ○ | ◎ | ◎ | ○ | | | | ○ | ○ | ◎ | ◎ | | | | | | | ◎ | ○ | ◆ | ◆ | ◎ | ○ | ◎ |
| 0.250 | ◆ | ◎ | ◆ | | | | | | ◎ | ◎ | ◎ | | | | | | | ○ | | ○ | | ◎ | ○ | ◎ |
| 0.300 | ◎ | ○ | ◎ | | | | | | ◎ | ◎ | ◎ | | | ◆ | ○ | | | | | | | | | |
| 0.350 | | | | | | | | | ◎ | ○ | ◎ | | | | | | | | | | | | | |
| 0.400 | ○ | ◆ | ○ | | | | | | ○ | ◎ | ◎ | | | | | | | | | | | | | |
| 0.500 | | ◆ | ◎ | | | | | | ◎ | ◆ | ◎ | | | | | | | | | | | | | |
| 0.600 | | ◆ | | | | | | | ◎ | ○ | ○ | | | | | | | | | | | | | |
| 0.700 | | | | | | | | | ○ | | ○ | | | | | | | | | | | | | |
| 0.800 | | ○ | ◎ | ◆ | | | | | ○ | ◆ | ◎ | | | | | | | | | | | | | |
| 1.000 | | | | | | | | | ◎ | | | | | | | | | | | | | | | |

Please consult with the Whole sales & support section

Please consult with the Whole sales & support section